

Appl. No. 10/675819
Reply to Office action of 3/10/05
Page 4

Please replace the paragraphs beginning at page 4, lines 2 and 12 with the following amended paragraphs:

Furthermore, the arrangement structure is also comprised of the following ~~manner~~s. A roof reinforcing member is provided on said roof member, while a side reinforcing member is provided on said side member. When both the roof reinforcing member and the side reinforcing member are connected to said connecting part, the strength of the roof member and the side member around the connecting part is ~~more~~ increased. Thereby, strength can be sufficiently secured for attaching the vehicle door open-close device and the gazette member to said roof member and the side member.

Still further, the arrangement structure is also comprised of the following ~~manner~~s. An attachment reinforcing member is provided on an attaching part of said inside roof member or said inside side member wherein said gazette member is attached thereto. The attachment reinforcing member is connected to said connecting ~~potien~~ portion. Thereby, strength can be sufficiently secured for attaching the vehicle door open-close device and the gazette member to said roof member and the side member.

p. 5 line 3
Please replace the paragraph beginning at page 4, line 1 with the following amended paragraph: *AM 5/26/02*

Fig.4A is an explanatory side view showing ~~a-substantial~~ substantially the arrangement position of the vehicle door open-close device in a vehicle room when a door is fully closed.